

DP

DP-9000EN

Dot Matrix Printer



Reliability

Speed

Versatility

- 24 pin - Excellent Print Quality
- Up to 864 Characters Per Second
- Prints up to 9-Part Forms
- Resident Barcodes

High Speed DP-9000EN Dot Matrix Printer offers 24-pin print head for crisp quality printouts and with blazing performance speed of up to 864 characters per second to fly through your longest jobs.

Excellent form handling with 16" width capability and multi-layer forms of up to 9 parts are just some of the features.

With a wide range of fonts and industry standard barcodes already resident in the printer, DP-9000EN is the ultimate printer for your printing applications.

Built upon our reputation of high performance printers – reliability, speed & versatility – the DP-9000EN is the best solution for the most demanding heavy duty printing jobs.

DP
Printing Solutions



Business Advantage

Heavy-Duty High Speed Printing in graphic Mode

- * High speed
DP-9000EN 1000 cps(SSD Mode,13.8cpi)
- * 7 resident LQ fonts
- * 1+8 multipart forms capability
- * 2 emulation modes :EPSON ESC/P2, IBM2391
- * 132-Kbyte data buffer
- * Interface : Centronics(IEEE 1284 NIBBLE)
RS-232C , USB(USB2.0 Fullspeed) and
10/100 Base-T Ethernet (standard Interface)

Configurations		DP-9000EN
Print Method		24-pin dot matrix impact bi-directional (text & graphics)
Print Speeds	Super Speed Draft	1000 cps(13.8cpi)
	Speed Draft(12cpi)	864 cps(12 cpi)
	Draft Pica(10cpi)	720 cps
	HQDR Pica(10cpi)	360 cps
	NLQ Pica(10cpi)	240 cps
	LQ Pica(10cpi)	180 cps
	Line feed speed	60 or 30 lines/second selectable
	EPPT draft	710 pph (page/hour)
	EPPT LQ	300 pph (page/hour)
Graphic print speed		10.5 ips, or 18.0 ips, or 24.0 ips(180/360DPI) 15.7 ips, or 18.0 ips or 31.5 ips (120/240DPI)
Line Feed Pitch		1/360 "
Charecters		Epson charecters sets ,IBM code pages
Resident fonts		Roman ,Sans-serif,Courier,Prestige ,Script,OCR-A,OCR-B
Attributes		Italic,condensed,bold,double-strike,double-width,double-high,superscript, subscript,overscore,underscore
Data Buffer		132 Kbytes
Paper Feed		Push tractor or friction
Paper path		Rear(fanfold) or Top (cut sheet)
Paper weight		53 to 105 g/m2(14 to 28 lbs) Cut sheet : 64 to 105 g/m2 (17 to 28 lbs.)
Paper width		5" to 16" (fanfold&cut sheet)
Multipart forms		Original plus 8 duplicates(1+8 copy)
Ribbon life		20 million charecters Spacial cassette-type black fabric ribbon
Dowload		Epson :128 dowload charecters IBM : 32 Kbytes
Interface		Centronics(parallel IEE1284 nibble),RS-232(serial),USB(USB2.0 Full speed) 10/100 Base-T Ethernet
Printhead life		500 million dots / pin(MCBF)
Power consumption		210 watts(maximum) / 2 watts (Sleep mode)
Power supply		AC 100-240v 50/60 Hz
Dimension (WxDxH)		620 x 305 x 260mm(24.4"x12.0"x10.2") 620 x 455 x 295mm(24.4"x17.9"x11.6") with paper rack and sound seal cover
Weight		Approx. 20 Kg (44.1 lbs)

DP Printing Solutions

DISTRIBUTOR IN THAILAND

PROFESSIONAL HI-TECH SUPPLIES CO.,LTD

573/28-29 Soi Ramkhamhaeng 39(Theleela 1),Ramkhanhaeng Rd.

Plubpla, Wangthonglang,Bangkok 10310

Tel. 02-559-2944-5,02-935-6461-3 Fax:02-559-0893

www.pts.co.th e-mail:info@pts.co.th

